

Serial Number: 10/629,857 OA dated 06/27/06 Amdt. dated 9/27/06

## IN THE CLAIMS:

Claim 1 (Currently amended): A <u>film for metallization, composed of a</u> polypropylene-based resin composition for metallized films, comprising:

- (A) 100 parts by weight of a propylene random copolymer produced in the presence of a metallocene catalyst, which has the properties (a-1) to (a-6):
- (a-1) propylene unit present at 88 to 99.5% by mol, and ethylene and/or butene structural unit present at 0.5 to 12% by mol,
  - (a-2) melt flow rate (MFR<sub>A</sub>) of 1 to 30g/10 minutes,
- (a-3) polydispersity index (PI), determined by the melt viscoelasticity analysis, of 2.4 to 4,
- (a-4) solubles contained at 20°C or lower, determined by cross fractionation chromatography (CFC), at 1.2% by weight or less, and the solubles having a weight-average molecular weight of 0.1×10<sup>4</sup> to 6.0×10<sup>4</sup>,
- (a-5) solubles contained at 40°C or lower, determined by cross fractionation chromatography (CFC), at 4.0% by weight or less, and the solubles having a weight-average molecular weight of 0.1×10<sup>4</sup> to 8.0×10<sup>4</sup>, and
- (a-6) melting point (Tp, determined by differential scanning calorimetry (DSC), of 115 to 150°C.
- (B) 0.01 to 6 parts by weight of a polyethylene resin having a density of 0.945 to  $0.980 \text{g/cm}^3$ , melt index (MI<sub>B</sub>) of 1 to 1000 g/10 minutes, and ratio of MI<sub>B</sub> to MFR<sub>A</sub>, i.e., (MI<sub>B</sub>/MFR<sub>A</sub>) ratio, of 0.7 to 1000,

Serial Number: 10/629,857 OA dated 06/27/06

Amdt. dated 9/27/06

(C) 0.01 to 0.7 parts by weight of an antiblocking agent having an average

particle size of 1.0 to 5.0 $\mu$ m, pore volume of 0.45mL/g to 1.7 mL/g, and wear rate of 100mg

or less,

(D) 0.01 to 0.5 parts by weight of an antioxidant having a molecular weight of 500

or more, and

(E) 0.005 to 0.5 parts by weight of a hydrotalcite-based compound,

wherein the film satisfies the following relationship:

1165<17×[HST]-[YM]<1670 (a)

(where [HST] is a heat seal temperature (unit: °C) at which the load is 3N, and [YM] is a

tensile modulus (unit: MPa) of the film).

Claim 2 (canceled):

Claim 3 (Currently amended): The film for metallization polypropylene-based resin

composition according to Claim 1 for metallized films, wherein said antioxidant (D) is a

phenol- and/or phosphorus-based one.

Claim 4 (Canceled):

Claim 5 (Canceled):

3

Serial Number: 10/629,857 OA dated 06/27/06 Amdt. dated 9/27/06

	Claim 6 (Cancelled):
Claim	Claim 7 (Currently amended): A metallized film comprising the film according to [[5]] 1 for metallization, metallized with a metal and/or its oxide.
	Claim 8 (Canceled):
	Claim 9 (Canceled):
	Claim 10 (Canceled):
	Claim 11 (Canceled):
	Claim 12 (Canceled):